



Image shown may not reflect actual package.

CONTINUOUS 1280 e kW 1600 kVA 50 Hz 1500 rpm 400 Volts

Caterpillar is leading the power generation marketplace with Power Solutions engineered to deliver unmatched flexibility, expandability, reliability, and cost-effectiveness.

FEATURES

FUEL/EMISSIONS STRATEGY

- Low Fuel consumption

DESIGN CRITERIA

- The generator set accepts 100% rated load in one step per NFPA 110 and meets ISO 8528-5 transient response.

FULL RANGE OF ATTACHMENTS

- Wide range of bolt-on system expansion attachments, factory designed and tested
- Flexible packaging options for easy and cost effective installation

SINGLE-SOURCE SUPPLIER

- Fully prototype tested with certified torsional vibration analysis available

WORLDWIDE PRODUCT SUPPORT

- Cat dealers provide extensive post sale support including maintenance and repair agreements
- Cat dealers have over 1,800 dealer branch stores operating in 200 countries
- The Cat® S•O•SSM program cost effectively detects internal engine component condition, even the presence of unwanted fluids and combustion by-products

CAT® 3516 TA DIESEL ENGINE

- Reliable, rugged, durable design
- Field-proven in thousands of applications worldwide
- Four-stroke-cycle diesel engine combines consistent performance and excellent fuel economy with minimum weight

CAT SR5 GENERATOR

- Matched to the performance and output characteristics of Cat engines
- Industry leading mechanical and electrical design
- Industry leading motor starting capabilities
- High Efficiency

CAT EMCP 4 CONTROL PANELS

- Simple user friendly interface and navigation
- Scalable system to meet a wide range of customer needs
- Integrated Control System and Communications Gateway

CONTINUOUS 1280 kW 1600 kVA

50 Hz 1500 rpm 400 Volts



FACTORY INSTALLED STANDARD & OPTIONAL EQUIPMENT

System	Standard	Optional
Air Inlet	<ul style="list-style-type: none"> • Single element canister type air cleaner • Service indicator 	<ul style="list-style-type: none"> <input type="checkbox"/> Dual element & heavy duty air cleaners <input type="checkbox"/> Air inlet adapters & shut-off
Cooling	<ul style="list-style-type: none"> • Radiator with guard • Coolant drain line with valve • Radiator fan and fan drive • Fan and belt guards • Cat® Extended Life Coolant* • Coolant level sensors 	<ul style="list-style-type: none"> <input type="checkbox"/> Duct flange <input type="checkbox"/> Heat exchanger and expansion tank <input type="checkbox"/> Coolant level switch gauge <input type="checkbox"/> Jacket water heater
Exhaust	<ul style="list-style-type: none"> • Dry exhaust manifold • Flanged faced outlets 	<ul style="list-style-type: none"> <input type="checkbox"/> Mufflers and Silencers <input type="checkbox"/> Stainless steel exhaust flex fittings <input type="checkbox"/> Elbows, flanges, expanders & Y adapters
Fuel	<ul style="list-style-type: none"> • Secondary fuel filters • Fuel priming pump • Flexible fuel lines • Fuel cooler* 	<ul style="list-style-type: none"> <input type="checkbox"/> Water separator <input type="checkbox"/> Duplex fuel filter <input type="checkbox"/> Primary Fuel Filter
Power Termination	<ul style="list-style-type: none"> • Bus bar (NEMA and IEC mechanical lug holes) • Top cable entry 	<ul style="list-style-type: none"> <input type="checkbox"/> Circuit breakers, UL listed, 3 pole with shunt trip, 100% rated, choice of trip units, manual or electrically operated (low voltage only) <input type="checkbox"/> Circuit breakers, IEC compliant, 3 or 4 pole with shunt trip (low voltage only), choice of trip units, manual or electrically operated <input type="checkbox"/> Bottom cable entry <input type="checkbox"/> Power terminations can be located on the right, left and/or rear as an option. Multiple circuit breaker options
Generator	<ul style="list-style-type: none"> • Class H insulation • Cat digital voltage regulator (CDVR) with kVAR/PF control, 3-phase sensing • Reactive droop 	<ul style="list-style-type: none"> <input type="checkbox"/> Oversize & premium generators <input type="checkbox"/> Winding temperature detectors <input type="checkbox"/> Anti-condensation heaters
Governor	<ul style="list-style-type: none"> • Woodward 2301 isochronous 	<ul style="list-style-type: none"> <input type="checkbox"/> Load share governor
Control Panel	<ul style="list-style-type: none"> • EMCP 4.2 • User Interface panel (UIP) - rear mount • AC & DC customer wiring area (right side) • Emergency stop pushbutton 	<ul style="list-style-type: none"> <input type="checkbox"/> Option for right or left mount UIP <input type="checkbox"/> Local & remote annunciator modules <input type="checkbox"/> Digital I/O Module <input type="checkbox"/> Generator temperature monitoring & protection <input type="checkbox"/> Remote monitoring software
Lube	<ul style="list-style-type: none"> • Lubricating oil • Gear type lube oil pump • Oil filter, filler and dipstick • Oil drain lines and valve • Fumes disposal 	<ul style="list-style-type: none"> <input type="checkbox"/> Oil level regulator <input type="checkbox"/> Deep sump oil pan <input type="checkbox"/> Electric & air prelube pumps <input type="checkbox"/> Manual prelube with sump pump <input type="checkbox"/> Duplex oil filter
Mounting	<ul style="list-style-type: none"> • Rails - Engine / generator / radiator mounting • Rubber anti-vibration mounts (shipped loose) 	<ul style="list-style-type: none"> <input type="checkbox"/> Isolator removal <input type="checkbox"/> Spring-type vibration isolator (shipped loose)
Starting/Charging	<ul style="list-style-type: none"> • 24 volt starting motor(s) • Batteries with rack and cables • Battery disconnect switch 	<ul style="list-style-type: none"> <input type="checkbox"/> Battery chargers (10 or 20 amp) <input type="checkbox"/> 45 amp charging alternator <input type="checkbox"/> Oversize batteries <input type="checkbox"/> Ether starting aid <input type="checkbox"/> Heavy duty starting motors <input type="checkbox"/> Barring device (manual) <input type="checkbox"/> Air starting motor with control & silencer
General	<ul style="list-style-type: none"> • Right hand service • Paint - Caterpillar Yellow (with high gloss black rails & radiator) • SAE standard rotation • Flywheel and flywheel housing - SAE No. 00 	<ul style="list-style-type: none"> <input type="checkbox"/> CSA certification <input type="checkbox"/> CE Certificate of Conformance <input type="checkbox"/> Seismic Certification per Applicable Building Codes: IBC 2000, IBC 2003, IBC 2006, IBC 2009, CBC 2007 * Not included with packages without radiators

CONTINUOUS 1280 ekW 1600 kVA

50 Hz 1500 rpm 400 Volts



SPECIFICATIONS

CAT GENERATOR

Cat Generator
Frame size..... 1625
Excitation..... Internal Excitation
Pitch..... 0.6667
Number of poles..... 4
Number of bearings..... Single bearing
Number of Leads..... 006
Insulation..... UL 1446 Recognized Class H with tropicalization and antiabrasion
Insulation..... Class F with tropicalization and antiabrasion
- Consult your Caterpillar dealer for available voltages
IP Rating..... IP23
Alignment..... Pilot Shaft
Overspeed capability..... 150
Wave form Deviation (Line to Line)..... 002.00
Voltage regulator..... 3 Phase sensing with selectable volts/Hz
Voltage regulation..... Less than +/- 1/2% (steady state)
Less than +/- 1% (no load to full load)
Telephone influence factor..... Less than 50
Harmonic Distortion..... Less than 5%

CAT DIESEL ENGINE

3516 TA, V-16, 4-Stroke Water-cooled Diesel
Bore..... 170.00 mm (6.69 in)
Stroke..... 190.00 mm (7.48 in)
Displacement..... 69.00 L (4210.64 in³)
Compression Ratio..... 13.5:1
Aspiration..... TA
Fuel System..... Electronic unit injection
Governor Type..... Woodward

CAT EMCP 4 SERIES CONTROLS

EMCP 4 controls including:

- Run / Auto / Stop Control
- Speed and Voltage Adjust
- Engine Cycle Crank
- 24-volt DC operation
- Environmental sealed front face
- Text alarm/event descriptions

Digital indication for:

- RPM
- DC volts
- Operating hours
- Oil pressure (psi, kPa or bar)
- Coolant temperature
- Volts (L-L & L-N), frequency (Hz)
- Amps (per phase & average)
- ekW, kVA, kVAR, kW-hr, %kW, PF

Warning/shutdown with common LED indication of:

- Low oil pressure
- High coolant temperature
- Overspeed
- Emergency stop
- Failure to start (overcrank)
- Low coolant temperature
- Low coolant level

Programmable protective relaying functions:

- Generator phase sequence
- Over/Under voltage (27/59)
- Over/Under Frequency (81 o/u)
- Reverse Power (kW) (32)
- Reverse reactive power (kVA) (32RV)
- Overcurrent (50/51)

Communications:

- Six digital inputs (4.2 only)
- Four relay outputs (Form A)
- Two relay outputs (Form C)
- Two digital outputs
- Customer data link (Modbus RTU)
- Accessory module data link
- Serial annunciator module data link
- Emergency stop pushbutton

Compatible with the following:

- Digital I/O module
- Local Annunciator
- Remote CAN annunciator
- Remote serial annunciator

CONTINUOUS 1280 ekW 1600 kVA

50 Hz 1500 rpm 400 Volts



TECHNICAL DATA

Open Generator Set - - 1500 rpm/50 Hz/400 Volts	DM8368	
Low Fuel Consumption		
Generator Set Package Performance Genset Power rating @ 0.8 pf Genset Power rating with fan	1600 kVA 1280 ekW	
Coolant to aftercooler Coolant to aftercooler temp max	82 ° C	180 ° F
Fuel Consumption 100% load with fan 75% load with fan 50% load with fan	337.2 L/hr 260.4 L/hr 188.3 L/hr	89.1 Gal/hr 68.8 Gal/hr 49.7 Gal/hr
Cooling System¹ Air flow restriction (system) Engine Coolant capacity with radiator/exp. tank Engine coolant capacity Radiator coolant capacity	0.12 kPa 398.0 L 233.0 L 165.0 L	0.48 in. water 105.1 gal 61.6 gal 43.6 gal
Inlet Air Combustion air inlet flow rate	107.1 m ³ /min	3782.2 cfm
Exhaust System Exhaust stack gas temperature Exhaust gas flow rate Exhaust flange size (internal diameter) Exhaust system backpressure (maximum allowable)	479.7 ° C 272.3 m ³ /min 203.2 mm 6.7 kPa	895.5 ° F 9616.2 cfm 8.0 in 26.9 in. water
Heat Rejection Heat rejection to coolant (total) Heat rejection to exhaust (total) Heat rejection to aftercooler Heat rejection to atmosphere from engine Heat rejection to atmosphere from generator	832 kW 1222 kW 136 kW 146 kW 57.5 kW	47316 Btu/min 69495 Btu/min 7734 Btu/min 8303 Btu/min 3270.0 Btu/min
Alternator² Motor starting capability @ 30% voltage dip Frame Temperature Rise	4978 skVA 1625 80 ° C	144 ° F
Lube System Sump refill with filter	401.3 L	106.0 gal
Emissions (Nominal)³ NOx mg/nm ³ CO mg/nm ³ HC mg/nm ³	8115.8 mg/nm ³ 354.8 mg/nm ³ 74.6 mg/nm ³	

¹ For ambient and altitude capabilities consult your Cat dealer. Air flow restriction (system) is added to existing restriction from factory.

² UL 2200 Listed packages may have oversized generators with a different temperature rise and motor starting characteristics. Generator temperature rise is based on a 40 degree C ambient per NEMA MG1-32.

³ Emissions data measurement procedures are consistent with those described in EPA CFR 40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NOx. Data shown is based on steady state operating conditions of 77°F, 28.42 in HG and number 2 diesel fuel with 35° API and LHV of 18,390 btu/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations. Emissions data is based on 100% load and thus cannot be used to compare to EPA regulations which use values based on a weighted cycle.

CONTINUOUS 1280 ekW 1600 kVA

50 Hz 1500 rpm 400 Volts



RATING DEFINITIONS AND CONDITIONS

Meets or Exceeds International Specifications: AS1359, CSA, IEC60034-1, ISO3046, ISO8528, NEMA MG 1-22, NEMA MG 1-33, UL508A, 72/23/EEC, 98/37/EC, 2004/108/EC

Continuous - Output available with non-varying load for an unlimited time. Average power output is 70-100% of the continuous power rating. Typical peak demand is 100% of continuous rated ekW for 100% of operating hours. Continuous power in accordance with ISO3046. Continuous ambients shown indicate ambient temperature at 100% load which results in a coolant top tank temperature below the alarm temperature.

Ratings are based on SAE J1349 standard conditions. These ratings also apply at ISO3046 standard conditions. **Fuel rates** are based on fuel oil of 35° API [16° C (60° F)] gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal.). Additional ratings may be available for specific customer requirements, contact your Cat representative for details. For information regarding Low Sulfur fuel and Biodiesel capability, please consult your Cat dealer.

CONTINUOUS 1280 ekW 1600 kVA

50 Hz 1500 rpm 400 Volts



DIMENSIONS

Package Dimensions		
Length	5905.4 mm	232.5 in
Width	2286.0 mm	90 in
Height	2342.0 mm	92.2 in
Weight	9072 kg	20,000 lb

NOTE: For reference only - do not use for installation design. Please contact your local dealer for exact weight and dimensions. (General Dimension Drawing #2882679).

Performance No.: DM8368

Feature Code: 516DE89

Gen. Arr. Number: 2523846

Source: U.S. Sourced

July 26 2011

17801915

www.Cat-ElectricPower.com

© 2011 Caterpillar
All rights reserved.

Materials and specifications are subject to change without notice.
The International System of Units (SI) is used in this publication.

CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.